



Clearguard

Activation

Barrier-Free Public Toilet Door Access Control

Wireless Technology – IP65

EASY TO USE

Large surface, soft touch push buttons make toilet entry/exit and door locking/unlocking easy for all.

ILLUMINATED

Open/Close buttons illuminate when pressed and the lock symbol on the external switch illuminates when access is attempted to a toilet cubicle already in use. Visual indication when the batteries need replacing.

WIRELESS

Simple push button registration of both the internal and external switches to our 2.4GHz wireless receiver.

AUDIO

Switches can be set to indicate the door position with a beep or spoken word. Audio indication will sound when the batteries need replacing.



Clearguard

Activation

Dimensions



Technical Specifications

Receiver (CG-Rx)

Power	DC12-30V/AC12-24V
Relay contact capacity	1A/30VDC, 0.5A/125VDC
Operating temperature	-20°C to 50°C
Product size	150 x 43 x 25mm
Current consumption	Standby: 30mA / Operation: 80mA (for DC 24V)

Internal Switch (CGI-Tx) / External Switch (CGE-Tx)

Rated frequency	2.455GHz
Battery	1.5V AAA – 4 per switch
Operating temperature	-20°C to 50°C
Product size	90 x 220 x 15mm
Ingress Protection	IP65

Parts included

Internal Switch CGI-Tx



External Switch CGE-Tx



Receiver CG-Rx



Cables



Double-sided tape x 4 pieces

