record STA 22H



Brief Specification

Configuration

record STA 22H sliding door operator with cushioned, noise reducing, replaceable track section and hinging cover

This operator is made to order in record's Sydney or Melbourne factories using Australian extruded aluminium profiles and Swiss manufactured electrical components.

Drive Type

Single sliding to 1×400 kg. Bi-parting to 2×300 kg

Locking

Motor brake locking with battery backup and integrated failsafe per BCA D2.19

Safety & Activation

record RIC 290 combination activation and safety sensors

Control

Option 1 - record BDE-D electronic mode pad

Option 2 - Lockitwell 4 position key switch, master keyable with AUTO, LOCK, OPEN and EXIT modes.

Egress

Green mushroom push button on stainless steel mounting plate.

Remote

Operator connected to building management system (mode selection) and Fire Trip (emergency open)

Pelmet

250mm standard profile. Anodised or powdercoat finish

Access

Option 1 - Card reader, by others.

Option 2 – Lockitwell spring return key switch, master keyable

Compliance

All sliding door operators and associated control devices and door panels must be designed and installed in accordance with

AS5007 - Powered Doors for Pedestrian Access and Egress, including one million cycle tested by a NATA accredited testing authority


Building Code of Australia

AS1428.1 - Design for Access and Mobility

AS1288 - Glass in Buildings

Warranty

2 years parts and 1 year labour, subject to all commissioning, service and maintenance, in accordance with AS5007 on the operator being conducted by authorised Agents or appointees during the warranty



record Automatic Doors Pty Ltd – www.recorddoors.com.au

Melbourne: 117 Scanlon Drive, Epping VIC 3076

Phone: +61 3 8339 2888 - 1300 804 438 - infomelbourne@recorddoors.com.au

3/463 Victoria Street, Wetherill Park NSW 2164 Sydney:

Phone: +61 2 8811 4000 - 1800 674 408 - infosydney@recorddoors.com.au

